



S E R I E S

---

STAINLESS STEEL  
**COOKWARE**



Suitable for use with the following:



GAS



ELECTRIC



CERAMIC



INDUCTION



DISHWASHER



## Stainless Steel Cookware

The Förje range of cookware is designed for professional cooking.

Designed with the high expectations of professional chefs in mind, Förje cookware is known for its robust construction and heat diffusing performance. With two grades of stainless steel (AISI 304 & AISI 430), encapsulating a 5 mm aluminium heat diffuser, this leading edge cookware is ideal for use on all heat sources including induction.

All items come complete with lids except frying pans and conical saucepans. Lids are available to suit.



### Stock pot

Model	Capacity (Lt)	Diameter (mm)	Height (mm)	Thickness (mm)
WSS8	8.0	240	205	0.8
WSS12	12.0	260	225	0.8
WSS16	16.0	280	260	0.8
WSS20	20.0	320	260	1.0
WSS24	24.0	340	265	1.0
WSS36	36.0	360	360	1.0
WSS50	50.0	400	400	1.0
WSS70	70.0	450	450	1.2
WSS98	98.0	500	500	1.2



### Casserole - High

Model	Capacity (Lt)	Diameter (mm)	Height (mm)	Thickness (mm)
CH2	2.4	160	120	0.8
CH4	4.4	200	140	0.8
CH7	7.2	240	160	0.8
CH11	11.1	280	180	0.5



### Casserole - Low

Model	Capacity (Lt)	Diameter (mm)	Height (mm)	Thickness (mm)
CL3	3.3	200	105	0.8
CL5	5.0	240	110	0.8
CL8	8.0	280	130	0.8
CL13	12.9	320	160	0.8



### Saucepan - High

Model	Capacity (Lt)	Diameter (mm)	Height (mm)	Thickness (mm)
SH2	2.4	160	120	0.8
SH4	4.4	200	140	0.8
SH7	7.2	240	160	0.8



### Saucepan - Low

Model	Capacity (Lt)	Diameter (mm)	Height (mm)	Thickness (mm)
SL1	1.0	140	75	0.8
SL1T*	1.0	140	75	0.8
SL2	1.9	160	95	0.8
SL3	3.3	200	105	0.8
SL5	5.0	240	110	0.8

\*T indicates the interior is Teflon® coated.



## Saucepan - Conical

Model	Capacity (Lt)	Diameter (mm)	Height (mm)	Thickness (mm)
CS1	1.00	160	60	0.8
CS2	1.60	200	65	0.8
CS3	2.75	240	75	0.8



## Frying pan

Model	Capacity (Lt)	Diameter (mm)	Height (mm)	Thickness (mm)
FP20	1.25	200	40	0.8
FP24	2.00	240	45	0.8
FP28	3.00	280	50	0.8
FP32	3.75	320	55	1.0
FP36	5.00	360	65	1.0
FP40	6.25	400	70	1.0



## Frying pan - Teflon® Coated

Model	Capacity (Lt)	Diameter (mm)	Height (mm)	Thickness (mm)
FP20T	1.25	200	40	0.8
FP24T	2.00	240	45	0.8
FP28T	3.00	280	50	0.8
FP32T	3.75	320	55	1.0
FP36T	5.00	360	65	1.0
FP40T	6.25	400	70	1.0



## Steamer

Model	Description	Thickness (mm)
ST234	Suits SL/SH/CL/CH2,3&4	0.6
ST78	Suits WSS8/CH7/SH7	0.8
ST12	Suits WSS12	0.8
ST16	Suits WSS16	0.8



## Frying pan - Extreme Performance

Model	Capacity (Lt)	Diameter (mm)	Height (mm)	Thickness (mm)
FP26XP	2.5	260	60	2.5
FP30XP	3.5	300	60	3.0
FP32XP	4.5	320	60	3.0



## Lids

Model	Diameter (mm)	Height (mm)	Thickness (mm)
L14	140	40	0.8
L16	160	50	0.8
L20	200	50	0.8
L24	240	50	0.8
L26	260	50	0.8
L28	280	50	0.8
L32	320	50	1.0
L34	340	50	1.0
L36	360	50	1.0
L40	400	50	1.0
L45	450	50	1.2
L50	500	50	1.2